## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 9 December 2004 (09.12.2004)

**PCT** 

(10) International Publication Number WO 2004/105939 A1

(51) International Patent Classification7:

B01J 27/18

(21) International Application Number:

PCT/KR2004/001068

(22) International Filing Date: 7 May 2004 (07.05.2004)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data: 10-2003-0033860

27 May 2003 (27.05.2003) KR

- (71) Applicant (for all designated States except US): LG CHEM. LTD. [KR/KR]; LG Twin Tower, East Tower 20, Yeouido-dong, Yeongdeungpo-gu, Seoul 150-721 (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KANG, Jun-han [KR/KR]; 354, Dong-myeon, Yeongi-gun, Chungcheongnam-do 339-860 (KR). LEE, Won-ho [KR/KR]; Gangbyeon Apt. 112-10, Mannyeon-dong, Seo-gu, Daejeon 302-741 (KR). JEONG, Sang-mun [KR/KR]; Chonggu Narae Apt. 108-1603, Jeonmin-dong, Yuseong-gu, Daejeon 305-729 (KR). PARK, Sang-ku [KR/KR]; Woosung Apt. 302-1106, Sadang 2-dong, Dongjak-gu, Seoul 156-773 (KR). CHAE, Jong-hyun [KR/KR]; Dungji Apt. 106-602, Dunsan 2-dong, Seo-gu, Daejeon 302-734 (KR).

- (74) Agent: CHO, In-Jae; 3rd Fl., Janghyun Bldg., 637-23, Yeoksam-dong, Gangnam-gu, Seoul 135-909 (KR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HYDROCARBON STEAM CRACKING CATALYST, METHOD FOR PREPARING THE SAME AND METHOD FOR PREPARING LIGHT OLEFIN BY USING THE SAME

(57) Abstract: Provided are a catalyst for hydrocarbon steam cracking for light olefin production and a method for preparing the same. The catalyst is a simple KMgPO<sub>4</sub> catalyst, a supported KMgPO<sub>4</sub> catalyst, or a KMgPO<sub>4</sub>-sintered catalyst. The simple KMgPO<sub>4</sub> catalyst is a catalyst containing KMgPO<sub>4</sub> as a catalyst component. The supported KMgPO<sub>4</sub> catalyst is prepared by impregnating a carrier with an aqueous solution of a KMgPO<sub>4</sub> precursor and the KMgPO<sub>4</sub>-sintered catalyst is prepared by mixing a KMgPO<sub>4</sub> powder or a KMgPO<sub>4</sub> precursor powder with metal oxide followed by sintering. Provided is also a method for producing light olefins such as ethylene and propylene by steam cracking in the presence of the catalyst. When the catalyst comprising KMgSO<sub>4</sub> as a catalytic component is used in olefin production, the yield of olefins is increased and the amount of cokes deposited on the catalyst is reduced, relative to a common steam cracking process. Therefore, catalyst activity can be maintained for a longer time.

